Rev: 9/1/21



Rough Rider Cut 32 - Specifications and Warranties

General:

Description:
Dye Method:
Dye Resolution:

- V

Fiber:

Tufted Face Weight:

Gauge: Pile Height: Primary Backing:

Secondary Backing:

Secondary Backing (optional):

Broadloom Width:

Origin:

Anti-Soil and Stain Protection:

StainSmart*

Antimicrobial Protection:



Performance:

Static Electricity:

Traffic:

Indoor Air Quality:

Flammability:

Radiant Panel: NBS Smoke Chamber: Methenamine Tablet:

Maintenance:

Spot Cleaning:

Professional Cleaning:

Commercial Limited Warranties:

10 Year 10% Fiber Loss Abrasive Wear Warranty 10 Year Texture Retention Warranty 10 Year Soil, Stains and Pet Urine Warranty Lifetime Antistatic Warranty

10 Year Tuft Bind Warranty

Cut pile broadloom and rugs

PrintWorks™ precision dye technology

400 dpi

WearOn® Nylon

32 oz / sqyd 1/10th

.22

Woven polypropylene

ActionBac

KangaTRAC polyurethane cushion

13'6" USA

StainSmart® triple-action protectant

- Repel Hydrophobic chemistry keeps spills from penetrating beyond the carpet surface
- Resist Blocks dye sites of fiber preventing stains from bonding
- Release Antistatic technology reduces attraction of debris to fiber

Impervion® antimicrobial technology

- · Resists growth of bacteria, mold, mildew
- Prevents discoloration and degradation of carpet
- Controls odors before they start

< 3.5 KV (AATCC-134)

Heavy commercial



Green Label Plus®

Certifies products exceed most stringent indoor air quality standards and are best suited for living, working, and learning environments

> 0.45 watts/cm2 (ASTM - E648, Class I)

< 450 flaming and non-flaming (ASTM-E662 NFPA-258)

Self-extinguishing (DOC FF-1-70)

Spot clean with approved carpet cleaner. Follow label directions.

Vacuum regularly
Hot water extraction

- Abrasive wear of surface pile guaranteed not to exceed 10%
- Guaranteed to maintain appearance under heavy foot traffic
- Provides total fiber coverage to protect against soil and stains
- Built-in static control fiber
- Guaranteed to maintain superior tuft bind in high traffic areas

